

Product data sheet

Product description	
Item number	SL-PS-AS3
Product name	primaSEAL self-adhesive sealing film
Sales unit	100 foils
Product features	
Applications	Long-term storage, short-term storage, transportation of sample material, storage of samples in/with solvents/acids
Sealing method	Self-adhesive; Adhesive strength depends on the pressure used
Composition and material	Soft PVC with polyacrylate; silicone-coated backing material
Transparent	Yes
Peelable	Yes
Pierceable	No
Solvent resistant	Yes
DMSO-resistant	Yes
Adhesive strength	Depending on the pressure used
Re-sealable	Yes
Film thickness	100 µm
Temperature range	-20 °C to +70 °C
With tear-off lip	Yes
Purity	Free from human DNA, nucleases and pyrogens
Sealing parameters	
Method	Sealing by pressure
Temperature	-
Time	-
Packaging	
Type of packaging	Bag
Piece/bag	100 pcs.
Storage conditions	
Temperature	15-27 °C
UV light / light	Store protected from light/UV light
Air humidity	< 80 %

Note: Improper storage of the goods can lead to discoloration and a reduction in product quality.

Steinbrenner Laborsysteme GmbH reserves the right to make changes in whole or in part at any time without prior notice.
The contents of this data sheet are confidential and the property of Steinbrenner Laborsysteme GmbH.
It may not be reproduced or made available to third parties without permission.



This document is also valid without a signature.

Version date: 18.10.2024