

Series	BT1250 Series 1250 µl Extended Length Barrier Tip		2370 Series 1250 µl Extended Length Barrier Tip	
Part Number	BT1250 BT1250.N	2370.N	2377 2377.N 2377.NS 2377.S	2372 2372.N 2372.NS 2372.S
Graduation Marks	Graduation marks are indicated at both 200 μ l, 500 μ l and 1000 μ l locations Refer to product image for visuals			
Tip Composition	Neptune pipette tips are made of virgin polypropylene			
Тір Туре	Natural Polypropylene and S ³ - Low Retention	Natural Polypropylene	Natural Polypropylene	and S ³ - Low Retention
Filter Material	High Density Polyethlene Filter	Density Polyethlene Filter Non-Filtered Products		
Offered in Sterile Format	Yes	No	Yes	
Configuration	Racked	Bulk	ESP Reload	Racked
Packaging Breakdown	96 tips/ rack 8 racks/ pack 4 packs/ case	1000 tips/ bag 4 bags/ case	96 tips/ card 10 cards/ pack 5 packs/ case	96 tips/ rack 8 trays/ pack 4 packs/ case
Autoclavable	No Autoclavable at 120°C for 10-15 minutes at 15 PSI			
Storage Condition	Store in a clean, dry environment at room temperature 15-30°C			

BT1250 Series

2370 Series





Product Specification Sheet

Quality Control:

Certificates of Compliance	Each lot undergoes stringent inspection and indiviadual lot testing ensures Neptune products are certified RNase, DNase, DNA and Endotoxin-free. Visit www.neptunescienfific.com to obtain a copy of a certificate of compliance for your Neptune product.	
RNase/ DNase	Products are washed in distilled water and concentrated via centrifugation. Samples are added to previously estab- lished nucleic acid standards, incubated for one hour at 37°C, and tested on a 2% gel using electrophoresis. Products must show no degradation of standards to pass. Test sensitivity is 10-7 Kunitz units/µl.	
Nucleic Acid	Products are washed in distilled water and concentrated via centrifugation. Then, samples are added to protocol spec- ified PCR reactions and thermal cycled for 50 cycles. A 2% agarose gel electrophoresis is used to examine experimental samples, positive controls, and negative controls. To pass, product samples must show no DNA amplification. Test sensitivity is 10 ng.	
Endotoxin/ Pyrogen	Products are tested for endotoxins by using the Limulus Amebocyte Lysate (LAL) gel assay according to FDA guidelines. Test sensitivity is 0.06 EU/ml.	
Sterilization	Products are sterilized using electron beam irradiation.	
Traceability	Each product contains a 5 digit lot number located on the rack, pack and case of each finished good. With Nep-tune's advanced manufacturing process all raw materials are able to be traced for maximum quality assurance.	

Advancements in Liquid Handling

S ³	Neptune's exclusive S ³ polymer was designed to increase pipetting accuracy by virtually eliminating tip retention and sample hold-up.
ESP Reload	Neptune's ESP (Environmental Sustainable Pack) was the industry's first pipette reload system designed to minimize plastic waste by 90% and provide an environmentally friendly solution.
Aerosol Barrier Tip	Specifically enginerred to reduce cross contamination.

Pipettor Compatibility:

BT1250 and 2370 Series Biohit Proline™ 1000 µl Brand Transferpette™ 1000 µl CLP Beta-Pette™ 1000 µl CLP Poseidon™ 1000 µl CLP Poseidon Electronic™ 1000 µl Eppendorf Reference™ 1000 µl Eppendorf Research[™] 1000µl Eppendorf Research Plus[™] 1000 µl Eppendorf Xplorer[™] 1000 µl Finnpipette[™] 1000 µl & 1200 µl Gilson Plpetman[™] P1000 Hamilton[™] 1000 µl Labnet BioPette E[™] 1200 µl Nichiryo Nichipet EX™ 1000 µl Socorex Calibri 822™ 1000 µl VWR Ergonomic High Performance™ 1000 µl VWR Ultra High Performance™ 1000 µl

